



Distributed by:



136 The East Mall
Toronto, Ontario
M8Z 5V5

Tele: 416 236-9610

Fax: 416 236-9611

Toll Free: 800-956-5630


HB "Mini" Level Transmitter

FEATURES:


- *Specifically designed for balance tank, CIP vessel, and other sanitary level control applications*
- *Rugged reliability in the harshest applications and environments*
- *Compact, ultra-sanitary package meets or exceeds requirements for Food, Beverage, Dairy and Bio-Pharmaceutical applications*
- *Fast shipment -(2-3 day standard)*

The "HB" has been specifically designed for use in simple level control applications such as *balance tanks* and *CIP vessels*. We understand the harsh environment typically encountered in such applications and have designed this product to stand up to direct wash-downs and wide variations in temperature. The sensor is available in two ranges for tanks 20" to 60" ("low range") and 60.1" to 100" ("high range").

Connections include 1.5" and 2" tri-clamp and all sensors are supplied with up to 100' of sealed, shielded cable (25' is standard). Internal compensation allows the transmitter to perform at temperatures up to 200° F (93° C) and withstand cleaning and sterilization to 250° F (121° C). Detailed specifications, ordering matrix and application information are listed on the reverse.



Complete Product Ordering Matrix



GENERAL SPECIFICATIONS

Environmental Specifications

Ambient Operating Temperature Range:	40°F to 120°F (4°C to 49°C)
Storage Temperature Range:	-40°F to 250°F (-40°C to 121°C)
Humidity:	0 to 95% RH, condensing

Material / Construction

Housing:	304 Stainless Steel, R _a 40 maximum finish
Wetted Parts:	316L Stainless Steel, R _a 25 maximum finish
Process Connection:	1-1/2" or 2" Tri-Clamp
Ratings:	NEMA 4X/IP-66, IP-67 3A Authorized
Standards:	Designed and manufactured to sound engineering practices in accordance with Article 3.3 of the PED 97/23/EC

Operating Specifications

Range:	HB1 0-20" to 0-60" Water Column HB2 0-60.1" to 0-100" Water Column
Accuracy:	Factory calibrated to +/-0.2% of Upper Range Limit (URL) Stabilized at 75°F (24°C)
Process Temperature Limits:	32°F to 250°F (0°C to 121°C) Compensated 32°F to 200°F (0°C to 93°C)
Temperature Stability:	Within +/-2.0%/100°F over the compensated process and ambient operational temperature range
Over-Range Capacity:	2.5 times Upper Range Limit
Response Time:	200 uSec
Power / Signal / Electrical	
Voltage:	12-40 VDC
Load Impedance:	1400 ohms (max) @ 40 VDC
Output:	4-20 mA DC, 2-wire
Electrical Ratings:	CE compliant

